

THE LOW-COST BUFFET-DISPENSER

JDM ID 3 - attractive design - easy refilling - automatic cleaning!
Perfect for smaller hotels, buffets, offices and kiosks.

- 3 drinks + chilled water (CO2 or hot - optional)
- 3x5 litre concentrate Bag-in-Box in the device (or even 1x10 litre + 1x5 litre)
- Preselection hot – optional (model Hot & Cold)
- Preselection CO2 – optional (model CO2)
- Small dimensions WxHxD: 400 x 590 x 420 mm
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Easy refilling
- Ease of use, programming, service and cleaning
- Service free dry cooling
- Perfect mixing result through patented MidMix®-system
- Multilingual ICD-Info Display
- Preparation for payment systems + accounting
- Reliable and made-to-last – premium materials, robust surfaces (no plastics)
- Decorative front panels (optional)



Inside view,
with 3 x 5 l
bag in box

ESI (easy-slide-in)
Product labels



Anti-
Vandalism
Buttons



Intelligent central
drink exit with LED

Available in the following versions:

JDM ID 3 STILL ECO, JDM ID 3 STILL, JDM ID 3 CO2,
 JDM ID 3 Hot & Cold

TECHNICAL DATA

DATEN	JDM ID 3 STILL ECO	JDM ID 3 STILL	JDM ID 3 CO ₂	JDM ID 3 Hot & Cold
Art. Nr.	frucB0331se	frucB0331	frucB0332	frucB0333
Width	400 mm	400 mm	400 mm	400 mm
Height	590 mm	590 mm	590 mm	590 mm
Depth	420 mm	420 mm	420 mm	420 mm
Exit height	160 mm	160 mm	160 mm	160 mm
Weight	34 kg	34 kg	38 kg	36 kg
Preselections	0	1	1	1
Product selection buttons (incl. water)	4	4	4	4
Automatic caraffe preselection (extra)	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
ESI product labels ²	✓	✓	✓	3
Flavours	3	3	3	3
Mixing ratio concentrates	1+4 ...1+49*	1+4 ...1+49	1+4 ...1+49	1+4 ...1+49
Bag-space dimensions WxDxH	380x300x200 mm	380x300x200 mm	380x300x200 mm	380x300x200 mm
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	18 l/h	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 v/ 50-60 hz	230 v/ 50-60 hz	230 v/ 50-60 hz	230 v/ 50-60 hz
Power max.	250 w	250 w	250 w	2.400 w
with CO ₂ -carbonator	-	-	✓	-
FSS ¹	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓
Dispensing area LED light	✓	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓	✓
Payment systems	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Monitoring Sanitation / Cleaning Interval	✓	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓	✓
Automatic cup sensor	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL

ALL our models are equipped with the unique and patented mixing system MidMix II.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV - syrup injection valve for perfect mixing result

*Installation of
water reduction
necessary

SIZE INCL. PACKAGING	JDM ID 3 STILL ECO	JDM ID 3 STILL	JDM ID 3 CO ₂	JDM ID 3 Hot & Cold
Width	570 mm	570 mm	570 mm	570 mm
Height	630 mm	630 mm	630 mm	630 mm
Depth	470 mm	470 mm	470 mm	470 mm
Weight incl. Packaging	36 kg	36 kg	40 kg	38 kg
MACHINE PACKAGE/PALLET				
Europallet 80 x 120 cm	4	4	4	4
UK-size pallet 100 x 120 cm	8	8	8	8

