

SPATIAL WONDER, ELEGANT AND TIMELESS!

THE JDM CT – OUR BEAUTIFULLY SHAPED MODEL,
THAT SAVES YOU VALUABLE COUNTER SPACE.

- 4/6 drink selection buttons + chilled water
- Bag-in-box concentrates are stored in existing furniture/base cabinet (for use of large bags eg. 10 litre)
- Preselection Hot or CO₂ – OPTIONAL (model Hot & Cold or CO₂)
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and made-to-last – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display
- Preparation for payment systems + accounting
- Carafe switch for quick serving by service staff
- Design of the drink dispense tower– OPTIONAL
- Base cabinet - OPTIONAL



JDM CT-S
Design



ESI (Easy
slide in)
labels

Standard delivery
contents



Wall instal-
lation

Available in the following versions:

JDM CT S-4/6 STILL, JDM CT S-4/6 CO₂,
JDM CT S4/6 Hot & Cold

DATA	JDM CT S-4 STILL	JDM CT S-4 CO2	CT S-4 Hot & Cold	JDM CT S-6 STILL	JDM CT S-6 CO2	CT S-6 Hot & Cold
Price in € excl. VAT	€	€	€	€	€	€
Art. Nr.	frucB0500	frucB0505	frucB0502	frucB0510	frucB0515	frucB0512
Control-/Dispensing unit with tower	S 4	S 4	S 4	S 6	S 6	S 6
Width	210 mm	210 mm	210 mm	210 mm	210 mm	210 mm
Height	425 mm	425 mm	425 mm	425 mm	425 mm	425 mm
Depth	200 mm	200 mm	200 mm	200 mm	200 mm	200 mm
Exit height	max 190 mm	max 190 mm	max 190 mm	max 190 mm	max 190 mm	max 190 mm
Weight	5 kg	5 kg	5 kg	5 kg	5 kg	5 kg
Preselections	1	1	1	1	1	1
Product selection buttons (incl. water)	5	5	5	7	7	7
Automatic carafe preselection (Extra)	✓	✓	✓	✓	✓	✓
ESI product labels ²	✓	✓	✓	✓	✓	✓
Flavours	4	4	4	6	6	6
Mixing ratio concentrates	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49
Concentrates in machine	-	-	-	-	-	-
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Dosage of preselection EXTRA/jug	max 2000ml	max 2000ml	max 2000ml	max 2000ml	max 2000ml	max 2000ml
Technics box	-	-	-	-	-	-
Width	260 mm	260 mm	260 mm	260 mm	260 mm	260 mm
Height	360 mm	360 mm	360 mm	360 mm	360 mm	360 mm
Depth	460 mm	460 mm	460 mm	460 mm	460 mm	460 mm
Weight	max. 23 kg	max. 27 kg	max. 25 kg	max. 24 kg	max. 28 kg	max. 26 kg
Distance technics box/ dispensing unit vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance technics box/ dispensing unit horizontal	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Distance concentrate/ technics box vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance concentrate/ technics box horizontal	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Cooling capacity	19 l/h	19 l/h	19 l/h	19 l/h	19 l/h	19 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	250 W	250 W	2600 W	250 W	250 W	2600 W
with CO2-carbonator	-	✓	-	-	✓	-
FSS ¹	✓	✓	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓	✓	✓
Dispense tower glass LED backlight	OPTIONAL	-	OPTIONAL	OPTIONAL	-	OPTIONAL
Dispensing area LED light	✓	✓	✓	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓	✓	✓	✓
Payment systems	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE
Syrup Injection Valve (SIV ³)	✓	✓	✓	✓	✓	✓
Water gallon + pumpset	OPTIONAL	OPTIONAL	-	OPTIONAL	OPTIONAL	-
Control of Disinfection and Sanitation intervals	✓	✓	✓	✓	✓	✓

ALL our models are equipped with the unique and patented mixing system MidMix II.

1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.

2) ESI = easy slide in: for fast and easy change of product labels

3) SIV - syrup injection valve for perfect mixing result

SIZE INCL. PACKAGING	JDM CT S-4 STILL	JDM CT S-4 CO2	CT S-4 Hot & Cold	JDM CT S-6 STILL	JDM CT S-6 CO2	CT S-6 Hot & Cold
Width	570 mm	570 mm	570 mm	570 mm	570 mm	570 mm
Height	590 mm	670 mm	590 mm	590 mm	670 mm	590 mm
Depth	310 mm	310 mm	310 mm	310 mm	310 mm	310 mm
Weight incl. Packaging	31 kg	35 kg	33 kg	32 kg	36 kg	34 kg
MACHINE PACKAGE/PALLET						
Europallet 80 x 120 cm	8	8	8	8	8	8
UK-size pallet 100 x 120 cm	12	12	12	12	12	12

